

# PU SEALANT CARTRIDGE

Product Description: Polyurethane Sealant for sealing and bonding substrates in the automotive industry – anodised aluminium, glass, wood, metal primers and concrete. Also suitable for bonding body panels and spoilers. Very flexible and resistant to weathering. Quick bonding, can be easily sanded.

VOC = 560 g/l. This product complies with Directive 2004/42/EC. The maximum voc for this product category in RFU state is 840 g/l  
Available in grey, white or black. SG 1.17 kg/l

Pre- Treatment: Must be applied on a thoroughly degreased substrate can be applied using a manual or pneumatic application gun.. Press the product firmly against the substrate for good adhesion. Clean tools with solvent immediately after use. Clean any excess sealant away with solvent before cured. After curing removal will be by mechanical means.

Skin forming time approx 60 mins @ 23°C

Curing time approx 24 hours @ 23°C (4mm)

Application temperature +5 - +35°C

Temperature resistance: -40 - +90°C



Information

For professional use only. Always consult the MB Coatings Health and Safety data sheets. Always read the risks and precautions stated on the product label.

The information contained in these pages is not intended to be exhaustive, and all persons using the product without first obtaining confirmation for MB Coatings as to the suitability of the product for the intended use, does so at their own risk. Whilst every effort is made to ensure the information given about the product (whether in this sheet or otherwise) is correct, we have no control over the quality or condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree to do so, we do not accept any liability arising out of use of the product. All information contained in this sheet is liable to modification from time to time, and we reserve the right to change the product in accordance with our policy of continuous product development. Expiry date – 12 months from production date in original packaging – store in the recommended temperature.

**MB PRODUCTS (UK) Ltd, t/a MB COATINGS, UNIT 230 AMPRESS PARK, LYMINGTON, HANTS SO41 8JW**

**TEL: 01590 677676, FAX: 01590 678578** [www.mbcoatings.co.uk](http://www.mbcoatings.co.uk)