

SEAM SEALANT - BRUSHABLE

Product Description: A fast drying sealant for sealing joints, welds and seams in car-body parts. It's a flexible product giving great protection against dirt and dust, water and moisture. When cured it doesn't crack and has a smooth layer which can be overpainted with lacquer systems (Test first is recommended due to the many types of paint available).

VOC = 360 g/l. This product complies with Directive 2004/42/WE. The maximum voc for this product category in RFU state is 840 g/l. Light grey.

Pre- Treatment: Must be applied on a thoroughly degreased substrate.
Pretreat surfaces with a suitable primer. The product should be applied to the surface in the required thickness. The layer should be left untouched until completely dry.

Can be applied with a putty knife or BRUSH.

Skin forming time approx 3-4 mins @ 25°C

Curing time approx 24 hours @ 25°C (1mm)

Over-paintable when fully cured.

Ambient temperature 15 - 35°C

Store in a sealed container, in cool and dry situation, away from heat sources and fire. Store away from direct sunlight.

Storage temperature 15 - 30°C



Information

For professional use only. Always consult the MB Coatings Health and Safety data sheets. Always read the risks and precautions stated on the product label.

The information contained in these pages is not intended to be exhaustive, and all persons using the product without first obtaining confirmation for MB Coatings as to the suitability of the product for the intended use, does so at their own risk. Whilst every effort is made to ensure the information given about the product (whether in this sheet or otherwise) is correct, we have no control over the quality or condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree to do so, we do not accept any liability arising out of use of the product. All information contained in this sheet is liable to modification from time to time, and we reserve the right to change the product in accordance with our policy of continuous product development. Expiry date – 12 months from production date in original packaging – store in the recommended temperature.

MB PRODUCTS (UK) Ltd, t/a MB COATINGS, UNIT 230 AMPRESS PARK, LYMINGTON, HANTS SO41 8JW

TEL: 01590 677676, FAX: 01590 678578 www.mbcoatings.co.uk