

UBS ANTI GRAVEL CARTRIDGE

Product Description: This product protects the car body from corrosion and minor stone hits. It's a strong, long lasting flexible layer which also gives protection against water, salt and oily substances. A thick layer can be applied and when cured can be over-lacquered.

VOC = 560 g/l. This product complies with Directive 2004/42/WE. The maximum voc for this product category in RFU state is 840 g/l
Available in Matt black.

Pre- Treatment: Must be applied on a thoroughly degreased substrate Can be applied over un-primed metal, aluminium and steel substrates, old lacquer coatings, polyester fillers, wash primers and stainless materials.

Polyester filler should be degreased and dry sanded P120.
Substrates to be degreased, dry sanded P220-P280 then degreased again.

Steel to be degreased, dry sanded P80-P120 and degreased again.

Galvanizes and aluminium to be degreased, dulled with abrasive cloth and degreased again.

Older coatings to be degreased, dry sanded P220-P280 and degreased again.

Pistol douching ex nozzle mm pressure 2 - 4 bar.

Dry time approx 40-60 mins @ 20°C

Store in a sealed container in a dry, cool situation.

Keep away from fire and heat sources and away from direct sunlight.



Information

For professional use only. Always consult the MB Coatings Health and Safety data sheets. Always read the risks and precautions stated on the product label.

The information contained in these pages is not intended to be exhaustive, and all persons using the product without first obtaining confirmation for MB Coatings as to the suitability of the product for the intended use, does so at their own risk. Whilst every effort is made to ensure the information given about the product (whether in this sheet or otherwise) is correct, we have no control over the quality or condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree to do so, we do not accept any liability arising out of use of the product. All information contained in this sheet is liable to modification from time to time, and we reserve the right to change the product in accordance with our policy of continuous product development. Expiry date – 12 months from production date in original packaging – store in the recommended temperature.

MB PRODUCTS (UK) Ltd, t/a MB COATINGS, UNIT 230 AMPRESS PARK, LYMINGTON, HANTS SO41 8JW

TEL: 01590 677676, FAX: 01590 678578 www.mbcoatings.co.uk