




STONE CHIP AEROSOL 500ml

Product Description: based on synthetic resins, the product is designed to protect car parts against the harmful effects of bad weather, salt, water, fuel and oil. It gives a strong, flexible anti-gravel layer and cuts down on noise. It can be coated with any lacquer system.
 VOC content for the mixture is 579 g/l. Therefore this product meets EU directive (2004/42/WE) which sets the VOC value for this product category (B/5), as 840g/l

Can be used over a multitude of substrates.

Pre- Treatment: Must be applied on a thoroughly degreased substrate. Colour – grey or black
 The steel surface should be degreased, dry ground (P80 – P120) and degreased again. The aluminium and galvanized surface should be degreased, dulled with abrasive cloth and degreased again. The old coatings should be degreased, dry ground (P220-P280) and degreased again. The plastic surface should be cleaned with water and detergent, dulled with abrasive cloth and degreased again.

 Application  Drying	<p>Shake the aerosol for 2 minutes and test spray on a piece of card. The best temperature is between 15 – 25°C and spray the surface from a distance of about 25 – 30cm. Apply 2 -3 layers waiting a couple of minutes between layers – shake can before putting on each layer.</p> <p>Clean the spray nozzle after use – hold the can pointing down and press the button emptying the content for about 5 seconds.</p> <p>One hour after the last layer, the surface can be coated with a auto paint and/or clear coat.</p> <p>Drying time is 40-60 minutes at 20°C</p>
 Information	<p>For professional use only. Always consult the MB Coatings Health and Safety data sheets. Always read the risks and precautions stated on the product label.</p>

The information contained in these pages is not intended to be exhaustive, and all persons using the product without first obtaining confirmation for MB Coatings as to the suitability of the product for the intended use, does so at their own risk. Whilst every effort is made to ensure the information given about the product (whether in this sheet or otherwise) is correct, we have no control over the quality or condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree to do so, we do not accept any liability arising out of use of the product. All information contained in this sheet is liable to modification from time to time, and we reserve the right to change the product in accordance with our policy of continuous product development. Stone Chip Spray has 3 years shelf life.

MB Products (UK) Ltd t/a MB COATINGS, UNIT 230 AMPRESS PARK, LYMINGTON, HANTS SO41 8JW

TEL: 01590 677676, FAX: 01590 678578

www.mbcoatings.co.uk